

Aqua-Pure®

WATER PURIFIERS

heavy duty filter housing for whole of house applications

Application: Dirt/Rust, Taste/Odour, Chlorine



AP801

- 1" or 1 1/2" BSP
- ≤80 lpm
- cold water



AP802

- 1" or 1 1/2" BSP
- ≤160 lpm
- cold water



Quality
Endorsed
Company
ISO 9001 Lic 3937
SAI Global

Manufactured under
a quality system
certified as
complying with
ISO 9001 by an
accredited
certification body

Features:

- 1" or 1 1/2" inlet/ outlet connections.
- Built in pressure relief button.
- Pressure tested high-impact plastic design.
- "Aqua-Grip" Filter wrench included.
- Manufactured from FDA CFR-21 compliant materials.
- 3 year limited warranty and **CUNOCare** technical support assistance.
- Mounting bracket included.

Benefits:

- For easy installation; high flow rates.
- Relieve pressure inside the filter for convenient cartridge changes.
- Protection against pressure surges and water hammer.
- Fast, effortless sump removal for changing cartridges.
- Conforms to public health requirements suitable for drinking and cooking water and all food applications.
- Guaranteed system design.
- Easy installation.

note: check cartridge flow rates recommended - rear page

models AP801/ AP802

replacement filter cartridges

(sold separately)

- whole of house applications
- high flow areas
- protects household plumbing

Premium performance filtration

Graded density cartridge construction for longer life!

Aqua-Pure dirt and rust cartridges are made from an exclusive process using pure white cellulose fibres. This unique process offers unsurpassed filtration performance.

• Longer life • Higher efficiency

As water passes from outer surface into the centre of the cartridge, the filtering pores become increasingly smaller to remove even microscopic particles. Unlike string wound and pleated paper cartridges, the rigid, sturdy construction of the Aqua-Pure cartridges are able to withstand high pressure drop and stressful conditions such as water hammer.

• Rigid construction • Resists water hammer

Note: Cartridges should be replaced every 6 months or sooner when noticeable pressure drop occurs.

For residential and light commercial applications

Your new Aqua-Pure Water Filter installs on the main cold water line entering the home.

Complete installation instructions included for you convenience.

Tools required for installation:

- Tube Cutter
- Teflon Tape
- Adjustable Wrench
- Appropriate Pipe Fittings

For AP801 housing



AP810-1
5 micron (nominal)
 flow rate ≤ 80 lpm
 reduces
 • sediment
 • dirt
 • rust



AP811-1
25 micron (nominal)
 flow rate ≤ 80 lpm
 reduces
 • sediment
 • dirt
 • rust



AP814-1
50 micron (nominal)
 flow rate ≤ 80 lpm
 reduces
 • sediment
 • dirt
 • rust



AP815-1
5 micron (nominal)
 flow rate ≤ 19 lpm
 reduces
 • sediment
 • turbidity
 • taste/odour
 • chlorine

For AP802 housing



AP810-2
5 micron (nominal)
 flow rate ≤ 160 lpm
 reduces
 • sediment
 • dirt
 • rust



AP811-2
25 micron (nominal)
 flow rate ≤ 160 lpm
 reduces
 • sediment
 • dirt
 • rust



AP814-2
50 micron (nominal)
 flow rate ≤ 160 lpm
 reduces
 • sediment
 • dirt
 • rust



AP815-2
5 micron (nominal)
 flow rate ≤ 38 lpm
 reduces
 • sediment
 • turbidity
 • taste/odour
 • chlorine

Specifications

Model No.	Inlet/ Outlet Size	Dimensions Maximum		Approx. Weight	Maximum Flow Rate	Clean Pressure Drop	Maximum Water Temp.	Maximum Water Pressure	Standard Replacement CTF. No.	Replacement CTG. Qty.	Degree of Filtration
		Height	Diameter								
AP801	1" or 1 1/2" BSP	30.6cm	20.6cm	2.5kg	≤ 80 lpm	N/A	40°C	900kpa	AP810	1	5 micron nominal (See above for other options)
AP802	1" or 1 1/2" BSP	60.0cm	20.6cm	3.7kg	≤ 160 lpm				AP810-2 sold separately		

LIMITED ONE YEAR WARRANTY

The Aqua-Pure AP801/AP802 systems are designed to operate at a maximum pressure of 900kPa (130psi) and at a maximum temperature of 40°C. Cuno Pacific Pty Ltd warrants this purifier to be free from defects in material and workmanship for a period of one year from the date of purchase (*Warranty period does not apply to cartridge which is consumable). This warranty is expressly limited to the repair or replacement at our premises of any part or parts proving defective providing the purifier has been installed in accordance with our Installation Instructions, all relevant Plumbing Codes, the installation of an approved Pressure Limiting Device preceding the purifier, and the pressure and temperature do not exceed the limits stated herein. This warranty does not extend to mechanical damage caused during installation or use. Save insofar as they may be excluded by law, this warranty is given in lieu of all other expressed or implied warranties or conditions and Cuno Pacific Pty Ltd shall in no event be held liable for damages or delays caused by defects and assumes no responsibility for unauthorised repairs.

The information contained within this brochure is accurate at the time of printing, but is subject to change without notice.

Cuno Pacific Pty Ltd

CUNOCare ☎ **1300 FILTER**
 3 4 5 8 3 7



cunoau@mmm.com

www.cuno.com.au

☎ **1800 671 599**

NEW ZEALAND
 3M New Zealand Ltd

Auckland

250 Archers Road, Takapuna 1332

Phone: 09 444 4760 Fax: 09 444 2773 email: innovation@nz.mmm.com web: www.3m.com/nz