

Aqua-Pure®

WATER PURIFIERS

shower filter



shower filter specifications

Slimline design with replaceable filter cartridge

- Shower filter part number - 11-SL
- Dimensions - 90mm dia - 80mm length
- Replacement cartridge part number - 41-SLC-PP
- Maximum operating pressure - 900kPa (130psi)
- Flow rate - 9 lpm

warranty

Your Aqua-Pure shower filter is designed to operate at a maximum pressure of 900kPa (130psi). Cuno Pacific Pty Ltd warrants this filter to be free of defects of material and workmanship for the period of one year from the date of purchase.

1 year
warranty

installation instructions

Read all instructions on reverse side carefully first and use teflon tape to seal all thread connections. The Aqua-Pure shower filter can be installed on the wall outlet (option 1) or, if your shower rose has a threaded connection, between the shower arm and the shower rose (option 2).

The shower filter comes with a water saver flow control disc inserted into the inlet of the shower filter. This disc will control the flow to approx 9 litres per minute to optimise the performance of the shower filter. A reduction in flow will be noticeable with high flow shower roses.

option 1

(wall installation – recommendation)

- Unscrew the existing shower arm leaving 1/2" BSP male thread exposed.
- Fit the 50mm long chrome adaptor onto the exposed thread.
- Remove the soft plastic plug from the inlet and screw the shower filter onto the adaptor male thread.
- Screw the existing shower arm onto the male outlet thread of the shower filter.
- Turn on the shower for 1-2 minutes to flush superficial dust and fines from shower filter cartridge.
Your shower now has clean filtered water!

option 2

(shower arm installation - if your shower rose has a threaded connection)

- Unscrew the existing shower rose.
- Remove the plastic plug from the inlet and screw the shower filter onto the male thread
on the shower arm.
- Screw the shower rose onto the outlet thread of the shower filter.
- Turn on the shower for 1-2 minutes to flush superficial dust and fines from shower filter cartridge.
Your shower now has clean filtered water!

how to change the shower filter cartridge...

- The filter cartridge should be replaced between 6-12 months depending upon water usage and chlorine levels in incoming water.
- When its life is exhausted the filter may clog, restricting water flow or more likely fails to remove chlorine odours.
- Separate the shower filter by unscrewing the main body anti-clockwise whilst the smaller section remains affixed.
- Remove and dispose of the old filter cartridge.
- Ensure the "O" rings are clear and slightly lubricated.
- Install the new cartridge and screw the main body clockwise onto the male threaded smaller section. **DO NOT OVERTIGHTEN.**
- Turn on the shower for 1-2 minutes to flush superficial dust and fines from shower filter cartridge. Your shower now has clean filtered water!



Aqua-Pure[®]
WATER PURIFIERS

Cuno Pacific Pty Ltd.

for technical assistance and product support, phone

CUNOcare 1300 367 362

email:- info@cuno.com.au website:- www.cuno.com.au

NEW ZEALAND Phone: 0800 355 185 Fax: 0800 355 181
3M New Zealand Ltd email: innovation@nz.mmm.com web: www.3m.com/nz



Quality
Endorsed
Company
ISO 9001 Lic 3937
SAI Global

Manufactured under
a quality system
certified as
complying with
ISO 9001 by an
accredited
certification body

